




## ET-500 intelligent bio ethanol fireplace

|                                  |   |                                   |   |
|----------------------------------|---|-----------------------------------|---|
| <b>Model</b>                     | ET-500  | <b>Brand</b>                      |  |
| <b>Suitable places</b>           | Lobby,halls,club,villa,outdoor,patio Etc.   |                                   |   |
| <b>Deminsion</b>                 | L500mm*W250mm*H235mm  | <b>Thickness</b>                  | 3-8mm ( Standard 3mm)   |
| <b>Reserved hole size</b>        | L470*W230(Internal hollow)  | <b>N.W.</b>                       | 18kg  |
| <b>Materials</b>                 | SUS/SPCC/AL   |                                   |   |
| <b>Ignition type</b>             | Button, remote control,or WIFI(optional)  |                                   |   |
| <b>igniter</b>                   | High energy Igniter(no deflagration,no shrill and no magnetic interference)   |                                   |   |
| <b>Fuel</b>                      | 75%-95% bio ethanol fireplace   |                                   |   |
| <b>Internal fuel capaticy</b>    | 2.5L  | <b>External fuel capaticy</b>     | Customised  |
| <b>Fuel Consumption</b>          | 0.6--8L/H   | <b>Calorific value</b>            | 12000BTU  |
| <b>Application of space area</b> | >23m2   | <b>Application spatial valume</b> | >78m3   |
| <b>Flame Height</b>              | 150-350mm   | <b>Venting system</b>             | Recommended   |
| <b>Supply power/Capacity</b>     | 110-240/50HZ,Ignition power :60W , continuous working:5W , fuel filling:15W   |                                   |   |
| <b>Material</b>                  | 1.The buttom is proceesed by SPOC black powder injection<br>2.The panel is made by SUS304/3.<br>3. burning tank is made by SUS304   |                                   |   |
| <b>Configuration</b>             | 1.Intelligent insert software 2.high-performance and low power consumption IC<br>3.Double protection and safe low voltage system 4.Automatic fuel filling system<br>5.Safe fuel filling system 6.Working protection security system 7.Double anti-overflow protection |                                   |   |
| <b>Options</b>                   | 1.External Extended Key Switch 2.WIFI Internet Access system 3.Mobile Terminal control system 4. Patented ventilation system 4.The indoor carbon dioxide control module 5.Stainless steel combustion frame  |                                   |   |
| <b>Accessories:</b>              | Warranty card,caution sign,AC adapter, Remote control,Fuel filling tube,Filter,installing handle,Clothing   |                                   |   |
| <b>Cerfications</b>              | CE、CMA、ROHS   |                                   |   |
| <b>Leading time</b>              | 10-15working days(bulk excepted)  |                                   |   |
| <b>Package deminsion</b>         | L580mm*330mm*310mm  |                                   |   |
| <b>G.W.</b>                      | 23kg  |                                   |   |
| <b>Warranty</b>                  | One year after factory date (refer to warranty card)  |                                   |   |